



广州市艾亮光电科技有限公司

广州总公司

广州市番禺区新造镇新广一路石博岭锦球工业园

Addr: Jinxu Industrial district, Shigangling, Xingyuan

Road, Xinze, Panyu District, Guangzhou, Guangdong, China

Tel: +86-20-34723703

Fax: +86-20-34724310

Website: www.edlite.hk

E-Mail: info@edlite.hk

香港公司

香港柴湾利文街11号宝源工业大厦二楼

Addr: 2/F, Haking (Tung Shing) Ind Bldg, 34 Lee Chung

Street, Cheai Wen, Hongkong

Tel: +852-2891 3058

Fax: +852-2891 8132

Web: <http://www.edlite.hk>

E-Mail: aaron@edlite.hk info@edlite.hk



艾亮LED照明
Edlite LED Illumination

公司简介

CORPORATE PROFILE

广州市艾亮光电科技有限公司自2003年成立伊始，一直潜心于标识/招牌用LED照明产品的研发，包括LED超薄灯箱，LED导光板，LED模组，LED日光灯，LED射灯条。经典打造的LED产品以其优良的品质、极具竞争力的性价比、强大的交货能力、优质的服务支持体系赢得了海内外广大用户的厚爱。

艾亮公司拥有SMD贴片模组自动化流水生产线，艾亮LED照明产品选用CREE、EPISTAR、CHIMEI等知名品牌的LED芯片；艾亮LED照明产品90%出口，客户遍及一百多个国家和地区，广泛应用于银行、证券所、交通系统(高速公路、机场、铁路和地铁)、医院、地下停车场、超市和体育场馆等。

诚信、为客户提供最优质的服务是艾亮的服务理念。我们将增加以往的致力于生产最优质的LED照明产品，努力把艾亮打造成为世界最好的LED照明生产厂家。广州艾亮LED照明产品将点亮您的品牌；让我们共同推动世界节能减排事业的发展。

Since establish in 2003, Guangzhou Edlie Company Limited always devote ourselves to research & development of LED illumination product. It is including LED slim light box, LED panel, LED module, LED tube, Flexible LED strip. Due to our high quality products, advanced LED control technology, most competitive cost-performance, strongest production and delivery capability and wonderful support and service system, Edlie has promptly gain a high reputation both at home and abroad.

Edlie have the robotized flow production line of SMD LED illumination product. We are only choice the CREE, EPISTAR, CHIMEI etc. well known brands. 90 percent of our products are exported to other countries and our customers cover in more than 100 countries and regions. They are widely used in Banks, Securities, Traffic System (highway, airport, railway and subway etc), Hospital, and Stadium etc.

Edlie's philosophy for management is to service our client with best quality and honesty. We will continue our effort in manufacturing best quality LED illumination product, and making Edlie Company Limited to be a first class LED illumination manufacturer around the world. Edlie LED illumination would light up your signs, let's make contributions to World Energy Conservation & Emission Reduction together.



P1

单面LED灯箱

SINGLE SIDED LED LIGHT BOX



ED-N2 磁条灯箱

Suck open, 17mm/0.67" thickness, silk printing
width is 30mm / 1.18", gray alu. finish



MTX-44-98 纤维布无框灯箱

Edge-ill design fabric LED light box, 44mm/ 1.73"
thickness. Gray alu. finish.



ED-S8 户外带锁灯箱

Lock open, 84mm/ 3.3" thickness, silk
printing width is 55mm/ 2.16", gray alu.
finish, backlit design, with backlit LED kit,
which is quite & easy installation.



ED-F9 轻巧型灯箱

Four sides snap open, 20mm/0.79"
thickness, frame width is
25mm / 0.98", frosted alu. finish.

Product Characteristic

LED strip is choice the long life design, 10 times than
the common LED slim light box.
Lightness difference is less than 10%, very equality.
Save 70% electricity than traditional light box.

产品特点

LED灯条采用长寿命设计, 10倍于普通LED灯箱;
灯箱亮度差异低于10%; 发光均匀;
比传统灯箱节约70%的电能。

P2

LED LIFE

双面LED灯箱

DOUBLE SIDED LED LIGHT BOX

◆Product Characteristic

Snap open design & suck open design & crystal design for you choice
 15-25mm / 0.59"-0.79" thickness
 Led strip is choice the long life design, 10 times than the common LED slim light box.
 Lightness difference is less than 10%, very equally.
 Save 70% electricity than traditional light box.

◆产品特点

翻盖设计 & 磁吸设计 & 水晶设计
 厚度仅为15-25mm;
 LED灯条采用长寿命设计, 10倍于普通LED灯箱;
 灯箱亮度差异低于10%, 发光均匀;
 比传统灯箱节约70%的电能。



ED-DP 双面水晶灯箱
 Crystal light box, 15mm/0.59" thickness, no any alu.



ED-F10 双面翻盖灯箱

Four sides snap open, 30mm/1.18" thickness, frame width is 25mm / 0.98", frosted alu finish.



ED-DF 双面灯箱

Four sides snap open, 40mm/1.57" thickness, frame width is 30mm / 1.18", gray alu finish.

P3

LED模组 & LED软灯条

LED MODULE & FLEXIBLE LED STRIP

◆Product Characteristic

Long lifespan;
 Low heat and high brightness;
 Easy to install yourself.

◆产品特点

长寿命;
 低耗能高亮度;
 容易安装使用;



LED 模组
 LED MODULE

Code	LED	Dimension	Voltage	Power	Lumen	Angle	Module	Fix
①	MD-K6288F1-2-X	3 pcs 320x	DC-12V	9.24	17	120	Sticker	Screw
②	BD-K6288F1-2-X	1 pcs 500x	DC-12V	9.24	18	120	Alu	Sticker
③	BD-K6288F1-2-X	4 pcs 368x	DC-12V	9.45	22	120	Alu	Sticker/Screw

1. LED can offer the Custom with spacing between each module.
 2. Color temperature: 300K, 3300K
 3. Working color: White/Green/Blue/Red/Yellow



LED 软灯条
 FLEXIBLE LED STRIP

◆Product Characteristic
 Maintenance free, easy installation with attached adhesives;
 Long life span 50,000+ hours;
 Solving the uneven luminous problem;
 Ultra-bright but ENERGY SAVING;

◆产品特点

维护简单, 容易安装;
 长寿命;
 可解决不均匀照明展示;
 高亮度低耗能;

Flexible LED strip (Indoor / Outdoor)							
Code	LED	Width	Qty of LED	Voltage	Power	Fix	Fix
①	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	3W/1M	3M HIKER	Sticker
②	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	3.2W/1M	3M HIKER	Sticker
③	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
④	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
⑤	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
⑥	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
⑦	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
⑧	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
⑨	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
⑩	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
⑪	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
⑫	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
⑬	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
⑭	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
⑮	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
⑯	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
⑰	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
⑱	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
⑲	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
⑳	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㉑	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㉒	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㉓	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㉔	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㉕	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㉖	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㉗	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㉘	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㉙	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㉚	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㉛	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㉜	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㉝	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㉞	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㉟	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㊱	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㊲	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㊳	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㊴	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㊵	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㊶	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㊷	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㊸	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㊹	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㊺	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㊻	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㊼	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㊽	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㊾	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker
㊿	EP-F12288E01-12	5x12	60/LED/1M	DC-12V	4.4W/1M	3M HIKER	Sticker

1. Color: Red/Green/Blue/White/Yellow
 2. Striping color: White/Green/Blue/Red/Yellow
 3. Striping color: White/Green/Blue/Red/Yellow
 4. The back with 3M tape easy to use

P4

LED日光灯 & LED灯泡

LED TUBE & LED BULB

LED 日光灯
LED TUBE

◆Product Characteristic

Solid-state, vibration resistant;
Low power consumption;
No buzzing noise, No fluorescent flickering;
No hazard of mercury or lead entering the environment;
Maintenance free, easy installation;
Long lifetime 50,000+ hrs. (5years).

LED Tube

Code	Length	Diameter	LED Qty of LED	Voltage	Material	Power	Light Effect
① E9-10309003-28	21.2*1030mm	Φ27*103mm	3028	DC-12V	Metallic	5	Transparent
② E9-10309003-20	41.2*1030mm	Φ27*103mm	150	DC-12V	Metallic	10	Transparent
③ E9-10309003-25	21.2*1030mm	Φ27*103mm	3028	AC 110-280V	Metallic	3	Transparent
④ E9-10309003-20	41.2*1030mm	Φ27*103mm	150	AC 110-280V	Metallic	6	Transparent
⑤ E9-10309003-25	21.2*1030mm	Φ27*103mm	3028	AC 110-280V	Metallic	12	Transparent
⑥ E9-10309003-20	41.2*1030mm	Φ27*103mm	150	AC 110-280V	Metallic	20	Transparent
⑦ E9-11012003-20	21.2*1030mm	Φ27*103mm	3028	AC 110-280V	Metallic	12	Transparent
⑧ E9-11012003-20	41.2*1030mm	Φ27*103mm	150	AC 110-280V	Metallic	20	Transparent

1. Emitting color: White/Green/Blue/Red/Yellow
2. Color temperature: 6000K, 3000K

◆产品特点

可靠, 防震;
低耗能;
无噪音, 无闪烁;
无公害, 无汞, 无铅;
安装维护简单;
长寿命;

◆Product Characteristic

Replaces 40 Watt traditional Light bulbs;
Long Life, up to 50,000+ hours;
Significantly reduces maintenance costs;

LED 灯泡
LED BULB

◆产品特点

直接替代40W白炽灯泡;
寿命长达50000小时;
有效的减少维护成本;

Code	Diameter	Length	Power	Lumen	Ra	Match
① E9-230-0-1000/733	E27mm	122mm	6W	30lm	90	E26/E27
② E9-230-0-1000/733	E27mm	122mm	6W	40lm	90	E26/E27
③ E9-230-0-1000/733	E27mm	122mm	6W	49lm	95	E26/E27

1. Emitting color: White/Green/Blue/Red/Yellow
2. Emitting color: 6000K, 3000K

LED bulb

P5

工程实例

PROJECT EXAMPLE



P6